



FasTrak™ Super Duty 48/54/60

FEATURES

- 48", 54" or 60" side-discharge decks with mulch kit option
- Heavy-duty, 7-gauge, full-height rear bumper with built-in hitch provides protection for the engine and exhaust, retains the ease of maintenance
- Simplest maintenance in the industry
- Standard hour meter
- 12.9 kph to get the job done fast!
- Commercial duty, sealed deck spindles
- SmoothTrak™ steering with patented automatic park brake system
- Very high blade tip speed for beautiful cut -- over 18,400 fpm
- Commercial hydrostatic transmissions for true zero turning radius manoeuvrability
- Commercial duty ZT 3100 transmissions
- Flex Fork™ Suspension

LIMITED
WARRANTY
4 YEAR | **800** HOUR
RESIDENTIAL

OR

LIMITED
WARRANTY
2 YEAR | **800** HOUR
COMMERCIAL

* See your local Hustler dealer for complete warranty details



Flex Fork™ Suspension Standard



* Original Purchaser Only





FastTrak Super Duty Specifications

More Engine Information

www.poweruplawncare.com.au/engines/

ENGINE SPECS

Kawasaki FX	24 HP	- 48" Deck
Kawasaki FX	26 HP	- 54"/60" Deck

Starter 12-volt, (see engine manufacturer specs)

Ignition Electronic

Charging System 12-volt, (see engine manufacturer specs for current rating)

Fuel Unleaded gasoline—maximum of 10% ethanol in fuel (see engine manufacturer specs)

Fuel Filter Replaceable, automotive-type

Air Filter Heavy-duty, canister style

Cooling Air cooled. Fly-wheel fan

Governor Mechanical

TRACTION DRIVE SYSTEM

Type Dual hydrostatic. Hydro-Gear ZT3100 commercial-duty pump/motor combination.

Hydrostatic Drive V-belt drive from engine crankshaft

Filter Spin-on type

Ground Speed

Forward: Infinitely variable: 0-8 mph (0-12.9 kph)
Reverse: 0-5 mph (0-8 kph)

Steering Twin-lever, SmoothTrak™ steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and true zero-degree-radius turns are all controlled with hand-operated controls

Turning Radius True zero radius. Turns within its own length. Counter-rotating, independent drive wheels

Brakes Service: Hydrostatic dynamic braking
Parking: Internal transmission mechanical brake. When steering levers are placed in neutral position, integral park brakes are automatically engaged.

Tyres Front: 13 x 5.0 – 6, rib tread
Drive: 48 in: 20 x 10 – 10, turf tread
54 in: 20 x 12 – 10, turf tread
60 in: 20 x 12 – 10, turf tread

Capacities

Fuel System: 6.3 US gal (23.84 l)

GENERAL INFORMATION

Safety Features Operator presence system connected to deck and drive clutches. Stabiliser rollers at rear of tractor.

Seat Moulded-vinyl seat with adjustable armrests. Fore and aft sliding adjustment. Seat-pan suspension springs standard.

Construction Mainframe is 1.5 in x 1.5 in x .188 in (38 mm x 38 mm x 4.8 mm) square steel tubing. Front caster wheels mounted with roller bearings on each wheel Front caster forks are .375 in (9.5 mm) steel

Controls Hand-operated choke/throttle, ignition switch, electric mower clutch. Integrated parking brakes

Indicators Hour meter, engine warning light (low oil pressure)

Cup Holder Two cup holders moulded into the left side fuel tank. Accommodates nearly any cup size.

DIMENSIONS

Height 41.8 in (1061.7 mm)

W/48 in Deck

Length 74.42 in (1890.2 mm)
Overall width: 50.3 in (1277 mm) w/discharge chute up
Tyre-to-tyre width: 47 in (1193.8 mm)
Weight: 835 lbs (378 kg)

W/54 in Deck

Length: 74.42 in (1890.2 mm)
Overall width: 56.2 in (1427 mm) w/discharge chute up
Tyre-to-tyre width: 51 in (1295.4 mm)
Weight: 860 lbs (390 kg)

W/60 in Deck

Length 75.92 in (1930 mm)
Overall width 62.7 in (1592.6 mm) w/discharge chute up
Tyre-to-tyre width 51 in (1295.4 mm)
Weight 885 lbs (401 kg)

DECKS

Side-Discharge 48", 54" or 60"

Type Free-floating deck using three blades with center blade to the front. Deck is suspended at the corners. Includes 4 deck-mounted rollers to improve flotation in rolling and uneven terrain

Construction 11 ga, .120 in (3.0 mm) welded steel with 11 ga, .120 in (3.0 mm) double welded onto spindle mount areas. Solid 1 in x .375 (25.4 mm x 9.5 mm) steel bars reinforce impact areas on trim edges. Commercial-style box-section reinforced front edge.

Cutting Heights Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (38 mm to 114.3 mm)

Mowing Blades Heavy-duty, heat-treated, high-lift steel
48 in: 16.5 in x 2.5 in x .20 in
54 in: 18.5 in x 2.5 in x .20 in
60 in: 20.5 in x 2.5 in x .20 in

Blade Tip Speed

48 in: 18,600 fpm
54 in: 18,910 fpm
60 in: 18,410 fpm

Deck Drive Single V-belt drive from engine with electric clutch to two spindles. Spring tension idler for extended belt life.

Spindles Aluminium casting with steel shafts and sealed ball bearings.

Discharge Chute High density, rubberised.

Width of Cut

48 in: 47.1 in (1200 mm)
54 in: 53.1 in (1350 mm)
60 in: 59.1 in (1500 mm)

Trim Capacity (left side)

48 in: 0.5 in (12.5 mm)
54 in: 2.5 in (65 mm)
60 in: 5.9 in (150 mm)

ACCESSORIES

2-Bag Catcher: Commercial-duty, 7.2 bushel, rear-mounted, two-bag catcher

Mulch Kit: Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

Other Accessories: Light Kit, Stripe Kit, Steering Lever Extension Kit

Specifications subject to change without notice.