



FasTrak™ Super Duty 36/42

FEATURES

- A true, commercial-duty unit in a compact package
- Commercial-duty ZT 3100
- SmoothTrak™ steering with patented automatic park brake system
- 20 HP Kawasaki FX engine
- Flex Fork™ Suspension

LIMITED
WARRANTY
4 YEAR | **800** HOUR
RESIDENTIAL

OR

LIMITED
WARRANTY
2 YEAR | **800** HOUR
COMMERCIAL

** See your local Hustler dealer for complete warranty details*



Flex Fork™ Suspension Standard

* LIMITED *
LIFETIME
WARRANTY
FRAME & LEADING EDGE OF DECK

** Original Purchaser Only*

poweruplawncare.com.au

PN 601449 2-11

PLP
POWERUP
LAWNCARE PRODUCTS

HUSTLER®



Cutting Grass Not Corners



FasTrak Super Duty Specifications

More Engine Information

www.poweruplawncare.com.au/engines/

ENGINE SPECS

Kawasaki FX 20 HP - 36"/42" Deck

Starter 12-volt, (see engine manufacturer specs)

Ignition Electronic

Charging System 12-volt, (see engine manufacturer specs for current rating)

Fuel Unleaded gasoline—maximum of 10% ethanol in fuel (see engine manufacturer specs)

Fuel Filter Replaceable, automotive-type

Air Filter Heavy-duty, canister style air cleaner to extend the service interval for excessive, dirty applications and improved performance.

Cooling Air cooled. Fly-wheel fan

Governor Mechanical

TRACTION DRIVE SYSTEM

Type Dual hydrostatic. Commercial-duty Hydro-Gear ZT3100.

Hydrostatic Drive V-belt drive from engine crankshaft

Filter Spin-on type

Ground Speed Forward: Infinitely variable: 0-7.5 mph (0-12.1 kph)
Reverse: 0-4.5 mph (0-7.2 kph)

Steering Twin-lever, SmoothTrak™ steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and true zero-degree-radius turns are all controlled with hand-operated controls.

Turning Radius True zero radius. Turns within its own length. Counter-rotating, independent drive wheels.

Brakes Service: Hydrostatic dynamic braking.
Parking: Internal transmission mechanical brake.
When steering levers are placed in open position, integral park brakes are automatically engaged.

Tyres Front: 13 x 5.0 – 6, rib tread
Drive: 36 in: 20 x 8.0 – 10, turf tread
42 in: 20 x 10.0 – 10, turf tread

Capacities

Fuel System: 6.3 US gal (23.84 l)

GENERAL INFORMATION

Safety Features Operator presence system connected to deck and drive clutches. Stabiliser rollers at rear of tractor.

Seat Moulded-vinyl seat with adjustable armrests. Fore and aft sliding adjustment. Seat-pan suspension springs standard.

Construction Mainframe is 1.5 in x 1.5 in x .188 in (38 mm x 38 mm x 4.8 mm) rectangular steel tubing. Drive motors mounted to .120 in (45 mm) welded steel. Front caster wheels mounted with roller bearings on each wheel. Front caster forks are .375 in (95 mm) steel.

Controls Hand-operated choke/throttle, ignition switch, electric mower clutch. Integrated parking brakes

Indicators Hour meter

Cup Holder Cup holder moulded into the left side fuel tank. Holds nearly any cup size.

DIMENSIONS

Height 40 in (1016 mm)

W/36 in Deck

Length 75.8 in (1926 mm)
Overall width: 37.76 in (959 mm) w/discharge chute up
Tyre-to-tyre width: 35.3 in (896 mm)
Weight: 680 lbs (308 kg)

W/42 in Deck

Length: 78.3 in (1989 mm)
Overall width: 44.62 in (1133 mm) w/discharge chute up
Tyre-to-tyre width: 38 in (965 mm)
Weight: 690 lbs (312 kg)

DECKS

Side-Discharge 36", 42"

Type Free-floating deck using two blades. Deck is suspended at the corners. Includes deck-mounted rollers to improve flotation in rolling and uneven terrain.

Construction 7 ga, .179 in (45 mm) welded steel with 11 ga, .125 in doubler welded onto spindle mount areas. Solid 1.5 in x .5 in (38.1 mm x 12.7 mm) steel bars reinforce impact areas on trim edges. Steel deck housing is 4 in (101.6 mm) deep which allows high-capacity mowing.

Cutting Heights Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (38 mm to 114.3 mm)

Mowing Blades Heavy-duty, heat-treated, high-lift steel

36 in: 1-13.75 in x 2.5 in x .20 in
1-20.5 in x 2.5 in x .20 in
42 in: 2-20.5 in x 2.5 in x .20 in

Blade Tip Speed

36 in: 18,400 fpm
42 in: 18,400 fpm

Deck Drive Single V-belt drive from engine with electric clutch to two spindles. Spring tension idler for extended belt life.

Spindles Aluminium casting with steel shafts and sealed ball bearings.

Discharge Chute High density, rubberised.

Width of Cut 36 in: 33.5 in (850.9 mm)
42 in: 40.25 in (1022.4 mm)

Trim Capacity (left side)

36 in: 0.5 in (12.7 mm)
42 in: 2.25 in (57.5 mm)

ACCESSORIES

Mulch Kit: Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass.

Other Accessories: Steering Lever Extension Kit, Light Kit

Specifications subject to change without notice.