



HUSTLER 3700

BUILT FOR ALL SEASONS

FEATURES

- 36 hp Shibaura liquid-cooled diesel engine for increased engine life
- Front-mounted, welded XR-7 deck, with tool-free installation
- XR-7 side-discharge decks rotate up 90 degrees with PTO shaft remaining connected for easier maintenance
- Cruise control and tilt and telescoping steering wheel
- Foldable, two-post ROPS
- Low noise and low vibration
- Excellent weight balance to achieve maximum stability
- One piece full open hood designed for simple access to engine
- Full-time automatic AWD with AWD lock
- Hydraulic weight transfer for maximum traction
- Full range of accessories and cabs
- One piece full open hood designed for simple access to engine
- Wet brakes in drive axle eliminate sticking, dirt and corrosion
- Foot pedal differential lock for extra traction

ACCESSORIES

- Beacon Kit
- ROPS Mounted Light Kit
- Auxiliary Hydraulic Kit
- Quick Attach System





Hustler Z Diesel Specifications

More Engine Information

www.poweruplawncare.com.au/engines/

TRACTOR
2 YEAR | **1500**
YEAR | HOUR

LIMITED WARRANTY

ENGINE
3 YEAR | **2000**
YEAR | HOUR

LIMITED WARRANTY

* See your local Hustler dealer for complete warranty details

ENGINE SPECS

Shibaura 36 HP

Type Liquid-cooled, inline, 3-cylinder, normally aspirated industrial diesel engine

Starter 12-volt (1.2 kw), solenoid shift positive engagement

Charging System 12-volt, 40-amp alternator

Oil Filter Spin-on engine oil filter 6.3 Qt (6.0 l) oil capacity

Fuel Capacity 13 US Gal (49.2 L)

Fuel Filter Heavy-duty, spin-on fuel filter, with sediment bowl

Injection System Bosch in-line, indirect injection

Air Filter Heavy-duty air filter with safety filter for maximum protection, dry, dual-element

Cooling Liquid cooled. Direct-driven, mechanical cooling fan

Cooling Capacity 3700 5.6 qt (5.4 L)

Governor Mechanical governor with 2700 RPM high idle speed

PTO Independent type PTO. PTO speed 2209 RPM

PTO Clutch Wet multi-disc manual

TRACTION DRIVE SYSTEM

Type Auto 4WD or Full time 4WD Hydrostatic transmission driving, two-speed gear axle

Filter 35 micron suction

Ground Speed Forward Low: 0-6 mph (0-9.5 kph) High: 0-15 mph (0-24 kph)
Reverse Low: 0-4 mph (0-6.5 kph) High: 0-9 mph (0-14.5 kph)

Steering Hydrostatic power. Tilt & telescoping steering wheel

Speed Control 2 pedals forward & reverse. 2 range hydrostatic transmission, cruise control

Brakes Wet disc (Single pedal control)

Tyres Front Drive 24 x 12 - 12, turf tread,
Rear Drive 20 x 8 - 10

Hydraulic Capacity 8.5 gal (32 L)

Weight (Power unit) 1653 lbs (750 Kg)

GENERAL INFORMATION

Safety Features Operator presence system connected to seat, traction pedals and park brake switch. Hand-operated parking brake. Two-post foldable ROPS.

Headlight Standard

Seat Suspension: Moulded-vinyl, adjustable seat with armrests. Fore and aft adjustment, suspension adjustment

Deck Lift Hydraulic w/adjustable weight transfer

Controls Hand-operated throttle, ignition switch, L-N-H & AWD Lock
Parking brake, hydraulic lift

Cup Holder Single cup holder

Indicators Hour meter, temp gauge, oil pressure light, charge light, glow plug light, audible alarm for high engine temperature and low oil pressure, air filter monitor, fuel gauge

DIMENSIONS

Height: 53 in (1300 mm) ROPS folded down
77 in (1750 mm) ROPS up

DECKS

72", XR-7™ Side-Discharge or 72" Rear-Discharge Decks

Deck Lift Raise and lower deck from driver's seat with simple hydraulic-operated deck lift.

Construction Welded steel. Solid 1.5 in x .50 in (38 mm x 12.5 mm) steel bars reinforce impact areas on trim edges. Reinforcements welded onto spindle mount areas. Steel deck housing is 5.5 in (140 mm) deep to provide room for high-capacity mowing.

Cutting Heights Height adjustment in .25 in increments from 2 in to 6 in (50 mm to 150 mm)

Mowing Blades Heavy-duty, heat-treated, high-lift steel Fusion™ blades. Fusion blades feature an exclusive electro-fusion technology that creates an ultra-hard layer at the blade's cutting edge, the blade remains sharp and continues to give a clean cut far longer than any blade on the market.

72 in: 24.50 in x 2.50 in x .230 in flat blade, high sail

Blade Tip Speed 72 in: 18,964 fpm

Blade Drive V-belt drive to all three spindles. Spring tension idler pulleys.

Spindles Machine ductile housing, 1 in (25.4 mm) diameter high carbon steel shafts and sealed ball bearings.

Discharge Chute Moulded Rubber: Over-center design allows for chute to be folded up for improved trailering or to pass thru gates, etc.

Width of Cut 72 in: 72 in (1830 mm)

Trim Capacity 72 in XR-7: 15.5 in (390 mm) (left side)