



# Hustler Fastrak™

## FEATURES

- 48" or 54" side-discharge decks with mulch kit option
- Beautiful quality of cut. Your lawn will be the envy of the neighbourhood
- Standard hour meter
- Simplest maintenance in the industry
- 0-8 mph (0-12.9kph) to get the job done fast
- Commercial duty sealed deck spindles
- Commercial duty ZT 3100 transmissions



LIMITED  
WARRANTY  
**4** YEAR | **400**  
YEAR | HOUR  
RESIDENTIAL

OR

LIMITED  
WARRANTY  
**1** YEAR | **400**  
YEAR | HOUR  
COMMERCIAL

*\* See your local Hustler dealer for complete warranty details*



*\* Original Purchaser Only*

[poweruplawncare.com.au](http://poweruplawncare.com.au)

PN 601449 2-11



# HUSTLER®



Cutting Grass Not Corners



# Hustler FasTrak Specifications

## More Engine Information

[www.poweruplawncare.com.au/engines/](http://www.poweruplawncare.com.au/engines/)

### ENGINE SPECS

Kawasaki FS 22 HP - 48" Deck

Kawasaki FS 24 HP - 54" Deck

**Starting** 12-volt (see engine manufacturer specs)

**Ignition** Electronic

**Charging System** 12-volt, (see engine manufacturer specs for current rating)

**Fuel** Unleaded gasoline - maximum of 10% ethanol in fuel (see engine manufacturer specs)

**Fuel Filter** Replaceable, automotive-type

**Cooling** Air cooled. Fly-wheel fan

**Governor** Mechanical

### TRACTION DRIVE SYSTEM

**Type** Dual hydrostatic. Commercial-duty Hydro-Gear ZT 3100.

**Hydrostatic Drive:** V-belt drive from engine crankshaft

#### Ground Speed

Forward: Infinitely variable. 0-8 mph (0-12.9 kph)

Reverse: 0-5 mph (0-8 kph)

**Steering** SmoothTrak™ twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls

**Turning Radius** True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

**Brakes** Service: Hydrostatic dynamic braking  
Parking: Internal transmission mechanical brake. When steering levers are placed in neutral position, integral park brakes are automatically engaged

**Tyres** Front: 13 x 5 - 6, rib tread  
Drive: **48 in:** 20 x 10 - 10, turf tread  
**54 in:** 20 x 12 - 10, turf tread

#### Capacities

Fuel System: 3.1 US gal (11.7 l)

### GENERAL INFORMATION

**Safety Features** Operator presence system connected to deck and drive clutches. Stabiliser rollers at rear of tractor

**Seat** Moulded-vinyl seat with adjustable armrests. Fore and aft sliding adjustment. Seat-pan suspension springs standard.

**Construction** Mainframe is 1.5 in x 1.5 in x .188 in (38 mm x 38 mm x 4.8 mm) square steel tubing. Front caster wheels mounted with roller bearings on each wheel Front caster forks are .375 in (9.5 mm) steel.

**Controls** Hand-operated choke, throttle, ignition switch, electric mower clutch. Integrated parking brakes.

**Indicators** Engine warning light.

**Cup Holder** Two cup holders moulded into the left side fuel tank. Accommodates nearly any cup size.

### DIMENSIONS

**Height** 41.8 in (1061.7 mm)

**W/48 in Deck** Length 74.42 in (1890.2 mm)  
Overall width: 50.3 in (1277 mm) w/discharge chute up  
Tyre-to-tyre width: 47 in (1193.8 mm)  
Weight: 835 lbs (378 kg)

**W/54 in Deck** Length: 74.42 in (1890.2 mm)  
Overall width: 56.2 in (1427 mm) w/discharge chute up  
Tyre-to-tyre width: 51 in (1295.4 mm)  
Weight: 860 lbs (390 kg)

### DECKS

**Side-Discharge** 48", 54"

**Type** Free-floating deck using three blades with center blade to the front. Deck is suspended at the corners. Includes 4 deck-mounted rollers to improve flotation in rolling and uneven terrain.

**Construction** 11 ga, .120 in (3.0 mm) welded steel with 11 ga, .120 in (3.0 mm) double welded onto spindle mount areas. Solid 1 in x .375 (25.4 mm x 9.5 mm) steel bars reinforce impact areas on trim edges. Commercial-style box-section reinforced front edge.

**Cutting Heights** Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (38 mm to 114.3 mm)

**Mowing Blades:** Heavy-duty, heat-treated, low-lift steel blades.  
48 in: 16.5 in x 2.5 in x .20 in  
54 in: 18.5 in x 2.5 in x .20 in

**Blade Tip Speed:** (at 3600 RPM engine speed)

48 in: 18,600 fpm

54 in: 18,910 fpm

**Deck Drive:** Single V-belt drive from engine with electric clutch to two spindles. Spring tension idler for extended belt life.

**Spindles:** Aluminium casting with steel shafts and sealed ball bearings.

**Discharge Chute** High density, rubberised.

**Width of Cut:** 48 in: 47.1 in (1196.3 mm)

54 in: 53.1 in (1348.7 mm)

**Trim Capacity:** (left side)

48 in: 2.0 in (50.8 mm)

54 in: 4.5 in (114.3 mm)

### ACCESSORIES

**2-Bag Catcher:** Commercial-duty, 7.2 bushel, rear-mounted, two-bag catcher with commercial belt-driven blower.

**Mulch Kit:** Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

**Flex Forks™:** Shock-absorbing front caster forks for a smooth ride and smoother cut

**Other Accessories:** Light Kit, Stripe Kit, Steering Extension Kit ROPS.