



Hustler Super Z

FEATURES

- HyperDrive™ Hydro System
Industrial Grade Pumps and Motors
- VX4™ Deck Technology provides the best finished appearance period!
- New 60", 66", or 72" side discharge decks
- 60" Rear discharge deck
- Simple design
- SmoothTrak™ Steering - responsive precise control
- Kawasaki engine options up to 37 HP
- 15 MPH/24 KPH
- Flex Fork™ Suspension

3 YEAR | **NO** HOUR LIMIT | **OR** **5** YEAR | **500** HOUR
 LIMITED WARRANTY | LIMITED WARRANTY
 * 3RD YEAR PARTS ONLY

5 YEAR | **3000** HOUR
 ON TRANSMISSIONS

** See your local Hustler dealer for complete warranty details*



Flex Fork™ Suspension Standard



LIMITED
LIFETIME
WARRANTY
 FRAME & LEADING EDGE OF DECK

** Original Purchaser Only*

PLP
 POWERUP
 LAWN CARE PRODUCTS





Hustler Super Z Specifications

More Engine Information

www.poweruplawncare.com.au/engines/

ENGINE SPECS

Kawasaki FX	31 HP (Rear Discharge)
Kawasaki FX	37 HP

Starter 12-volt

Ignition Electronic

Charging System 12-volt (see engine manufacturer specs)

Fuel Unleaded gasoline (see engine manufacturer specs)

Fuel Filter Replaceable, automotive-type

Air Filter Heavy-duty air cleaner to extend the service interval for excessive,

dirty applications and improved performance

Cooling Air cooled. Fly-wheel fan

Governor Mechanical

TRACTION DRIVE SYSTEM

Type Dual hydrostatic. Individual pumps power two direct-drive wheel motors. Hydrostatic system operates on 15W50 Mobil 1 synthetic motor oil. Transmission drive (oil) cooler for increased system life.

Pumps Two variable displacement, slipper piston pumps. Each pump powers one drive-wheel.
Sauer Danfoss DDC-20

Pump Drive B Section V-belt drive from engine crankshaft. Large pulley and idler diameters for longer belt life.

Hydraulic Lines Stainless-steel, high-pressure lines with Parker SealLok™ O-Ring Face-Seal fittings.

Cooling Large capacity cooler with 9 inch (228mm) fan for extended hydraulic life

Final Drive Direct-drive high-torque wheel motors. One for each drive wheel.

Parker TGO280 with hot oil shuttle

Filter Internal

Ground Speed Infinitely variable: 0–15 mph (0–24.14 kph) forward, 0–7.5 mph (0–12.07 kph) reverse

Steering SmoothTrak™ twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls

Turning Radius True zero turning radius. Turns within its own length.

Counter-rotating, independent drive wheels

Brakes Service: Hydrostatic dynamic braking

Parking: Automotive-style drum brakes. When steering levers are placed in neutral position, integral park brakes are automatically engaged

Tyres Front: 13 x 6.50 – 6, smooth tread, semi pneumatic

Drive: 24 x 12 – 12, turf tread

Capacities Fuel System: 12 US gal (45.4 l)

Hydraulic Oil: 3 US gal (11.36 l)

GENERAL INFORMATION

Safety Features Standard foldable ROPS with seat belt. Operator presence system connected to seat, deck clutch and park

brake switches. Stabiliser wheels at rear of lawn mower. Side discharge deck with discharge chute and rear discharge deck with deflectors.

Seat Super deluxe seat with armrests. Fore and aft adjustment. OR Moulded vinyl suspension seat with armrests Fore and aft adjustment.

Construction Main frame is 1.5 in x 3 in x .187 in (38 mm x 76.2 mm x 4.7 mm) rectangular steel tubing with internal gusset in frame bend. Drive motors mounted to 7 ga (4.5 mm) welded steel. Front caster wheels mounted with ball bearings on each wheel. Front caster forks are .5 in (12.7 mm) steel

Controls Hand-operated choke, throttle, ignition switch, electric mower clutch. Integrated parking brakes

Indicators Hour meter, engine warning light

Cup Holder Cup holder moulded into the left side fuel tank. Accommodates nearly any cup size.

DIMENSIONS

Height 54 in (1370 mm) ROPS folded down / 71.5 in (1816 mm) ROPS up

W/60 in Deck

Length: 84.5 in (2146 mm)

Overall width: 66 in (1676 mm) w/discharge

chute up Tyre-to-tyre width: 57 in (1447.8 mm)

Weight: 1515 lbs (687.2 kg)

W/66 in Deck

Length: 85.0 in (2159 mm)

Overall width: 72 in (1828.8 mm) w/discharge

chute up Tyre-to-tyre width: 60 in (1524 mm)

Weight: 1560 lbs (707.6 kg)

W/72 in Deck

Length: 86.7 in (2202 mm)

Overall width: 78 in (1981.2 mm) w/discharge

chute up Tyre-to-tyre width: 60 in (1524 mm)

Weight: 1600 lbs (725.75 kg)

DECKS

Side-Discharge 60", 66" or 72" VX4™

Type Free-floating deck using three blades with center blade to the front. Mower deck is suspended at the corners. Includes 3 standard deck-mounted rollers to improve flotation in rolling and uneven terrain.

Deck Lift Raise and lower deck from driver's seat with simple foot-operated deck height adjustment. Pin for setting height, transport position. Change cutting heights, climb curbs and trailer more easily.

Construction Welded steel. Solid 1.5 in x .375 (38 mm x 9.5 mm) steel bars reinforce impact areas on trim edges. Commercial style, box section reinforced front edge. Reinforcements welded onto spindle mount areas. High density, rubberised discharge chute.

Cutting Heights Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1 in to 5.5 in (25.4 mm to 139.7 mm).

Mowing Blades Heavy-duty, heat-treated, high-lift steel Fusion™ blades. Fusion blades feature an exclusive electro-fusion technology that creates an ultra-hard layer at the blade's cutting edge, the blade remains sharp and continues to give a clean cut far longer than any blade on the market.

60 in: 20.50 in x 3.00 in x .250 in blade, extra high sail

66 in: 22.50 in x 3.00 in x .250 in blade, extra high sail

72 in: 24.50 in x 3.00 in x .250 in blade, extra high sail

Blade Tip Speed

Side-Discharge

60 in: 18,630 fpm

66 in: 18,230 fpm

Rear-Discharge

60 in: 18,630 fpm

72 in: 18,550 fpm

Deck Drive Single V-belt drive from engine with electric clutch to all three spindles. Spring tension idler and large pulleys to extend belt life.

Spindles Ductile iron casting with steel shafts and sealed ball bearings

Width of Cut

Side-Discharge

60 in: 59.25 in (1505 mm)

66 in: 65.25 in (1657 mm)

Rear-Discharge

60 in: 59.10 in (1501.1 mm)

72 in: 71.25 in (1809 mm)

Trim Capacity (left side)

Side-Discharge

60 in: 2.5 in (63.5 mm)

66 in: 4.0 in (101.6 mm)

Rear-Discharge

60 in: 1.0 in (25.4 mm)

72 in: 8.0 in (203.2 mm)

ACCESSORIES

Catcher: Commercial-duty, 12 bushel, rear-mounted, three-bag catcher

Mulch Kit: Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil.

Gator™ Blades: Patented mulching blade design

Wavy Blades: Improved performance for mulching

Other Accessories: Hitch Kit, Light Kit, Hydraulic Deck Lift, Pneumatic Tire, Steering Lever Extension Kit, Rear Anti-Scalp wheel, Sand Kit, Stripe Kit.

Specifications subject to change without notice.