



Hustler X-ONE™

2 YEAR | **NO** HOUR LIMIT | **OR** **4** YEAR | **500** HOUR
LIMITED WARRANTY | **LIMITED WARRANTY**

** See your local Hustler dealer for complete warranty details*

FEATURES

- Proven separate pumps and motors
- New 48", 54" or 60" side discharge decks with VX4™ Technology
- 31 hp
- 11 mph/17.7 kph
- Flex Fork™ Suspension



Flex Fork™ Suspension Standard



** Original Purchaser Only*





Hustler X-One Specifications

More Engine Information

www.poweruplawncare.com.au/engines/

ENGINE SPECS

Kawasaki FX 31 HP

Starter 12-volt

Ignition Electronic

Charging System 12-volt (see engine manufacturer specs)

Fuel Unleaded gasoline (see engine manufacturer specs)

Fuel Filter Replaceable, automotive-type

Air Filter Heavy-duty air cleaner to extend the service interval for excessive,

dirty applications and improved performance

Cooling Air cooled. Fly-wheel fan

Governor Mechanical

TRACTION DRIVE SYSTEM

Type Dual hydrostatic. Individual pumps power two direct-drive wheel motors.

Hydrostatic system operates on 20W50 motor oil.

Pumps Two variable displacement, axial-piston type. Each pump powers one drive-wheel motor. Hydro-Gear PK 12cc Pump

Pump Drive V-belt drive from engine crankshaft

Hydraulic Lines Stainless-steel, high-pressure lines with Parker Seal-Lok™ O-Ring Face-Seal fittings.

Final Drive Direct-drive high-torque wheel motors. One for each drive wheel. Parker TFO240

Filter Internal

Ground Speed Forward: Infinitely variable: 0–11 mph (0–17.7kph) / Reverse: 0–6 mph (0–9.6kph)

Steering SmoothTrak™ twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls

Turning True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

Brakes Service: Hydrostatic dynamic braking. Parking: Automotive-style drum brakes. When steering levers are placed in park position, integral park brakes are automatically engaged.

Tyres Front: 13 x 6.5 – 6, rib tread

Drive: 54: 23 x 9.5 – 12, 60: 24 x 12.0 – 12

Capacities Fuel System: 10.4 US gal (39.36l)

GENERAL INFORMATION

Safety Features Standard foldable ROPS with seat belt. Operator presence system connected to seat, deck clutch and park brake switches. Stabiliser wheels at rear of lawn mower. Side discharge deck with discharge chute and rear discharge deck with deflectors.

Seat Deluxe vinyl seat with armrests. Fore and aft sliding adjustment.

Construction Main frame is 1.5 in x 2.0 in x .188 in (38mm x 50.8mm x 4.7mm) square steel tubing. Front caster wheels mounted with sealed ball bearings on each wheel. Front caster forks are .375 in (9.5 mm) steel

Controls Hand-operated choke, throttle, ignition switch, electric mower clutch.

Integrated parking brakes

Indicators Engine warning light (low oil pressure)

Cup Holder Cup holder moulded into the left side fuel tank.

ROPS Certified, 2-post, foldable ROPS with seatbelt.

DIMENSIONS

Height

53.00 in (1333.5 mm) With ROPS folded

71.25 in (1724.7 mm) With ROPS up

W/48 Side-Discharge Deck

Length: 80.8in (2052.3mm)

Overall width: 53.50in (1358.9mm) w/discharge chute up

Tyre-to-tyre width: 47in (1193.8 mm)

Weight: 1200 lbs (544 kg)

W/54 Side-Discharge Deck

Length: 80.8 in (2052.3 mm)

Overall width: 59.25in (1505.0mm) w/discharge chute up

Tyre-to-tyre width: 47in (1295.4 mm)

Weight: 1210 lbs (548 kg)

W/60 Side-Discharge Deck

Length: 83.25 in (2114.6 mm)

Overall width: 66in (1680 mm) w/discharge chute up

Tyre-to-tyre width: 54in (1376mm)

Weight: 1260 lbs (571 kg)

DECKS

Side-Discharge 48", 54" or 60" VX4™

Type Free-floating deck using three blades with center blade to the front.

Includes 3 deck-mounted rollers to improve flotation in rolling and uneven terrain.

Deck Lift Raise and lower deck from driver's seat with simple foot-operated deck height adjustment. Pin for setting height, transport position. Change cutting heights, climbing curbs and trailer more easily.

Construction Welded steel. Solid 1.5 in x .375 (38mm x 9.5 mm) steel bars reinforce impact areas on trim edges. Commercial style, box section reinforced front edge.

Reinforcements welded onto spindle mount areas. High density, rubberised discharge chute.

Cutting Heights Foot-operated deck height adjustment.

Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.0 in to 5.5 in (25.4 mm to 139.7 mm)

Mowing Blades Heavy-duty, heat-treated, high-lift steel Fusion™ blades. Fusion blades feature an exclusive electro-fusion technology that creates an ultra-hard layer at the blade's cutting edge, the blade remains sharp and continues to give a clean cut far longer than any blade on the market.

48 in: 16.5 in x 2.5 in x .20 in

54 in: 18.5 in x 2.5 in x .20 in

60 in: 20.5 in x 2.5 in x .20 in

Blade Tip Speed (at 3600 RPM engine speed)

Side-Discharge

48 in: 18,580 fpm

54 in: 18,340 fpm

60 in: 18,410 fpm

Deck Drive Single V-belt drive from engine with electric clutch to all three spindles.

Spring tension idler and large pulleys to extend belt life.

Spindles Ductile iron casting with steel shafts and sealed ball bearings.

Width of Cut Side-Discharge

48 in: 47.25 in

54 in: 53.25 in

60 in: 59.25 in

Trim Capacity (left side)

48 in: 0.5 in (12.5 mm) w/9.5 in tyre = 0.75 in (19 mm)

54 in: 2.5 in (65 mm) w/9.5 in tyre = 4.75 in (120.6 mm)

60 in: 5.9 in (150 mm) w/12 in tyre = 5.75 in (146.0 mm)

ACCESSORIES

Mulch Kit: Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

Catcher: Commercial-duty, 12 bushel, rear-mounted, three-bag catcher

No-Flat Caster Tyres: (Semi Pneumatic)

Gator™ Blades: Patented mulching blade design

Wavy Blades: Improved performance for mulching

Other Accessories: Light Kit, Steering Lever Extension Kit, Optional Rear Anti-Scalp wheel, Stripe Kit, Hitch Kit, Sand Kit, Suspension Kit for seat.

Specifications subject to change without notice.